




IEEE 1394 Common Mode Choke



- Designed for IEEE 1394 and other high-speed twisted pair interfaces.
- Shielded 1812 size filter
- Provides over 21 dB attenuation of common mode noise at 400 MHz with a cutoff frequency of 1.2 GHz

Core material Ferrite

Terminations RoHS compliant gold over nickel over moly-manganese

Weight: 30 mg

Ambient temperature -40°C to +85°C with Irms current.

Maximum part temperature +100°C (ambient + temp rise).

Storage temperature Component: -40°C to +100°C.

Tape and reel packaging: -40°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Failures in Time (FIT) / Mean Time Between Failures (MTBF)

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

Packaging 600/7" reel; 2200/13" reel Plastic tape: 12 mm wide, 0.25 mm thick, 8 mm pocket spacing, 3.9 mm pocket depth

PCB washing Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787_PCB_Washing.pdf](#).




Part number ¹	Common mode peak impedance (kOhms)	Cutoff frequency ² (GHz)	Common mode attenuation typ (dB)			Inductance ³ min (nH)	DCR max ⁴ (Ohms)	Isolation ⁵ (Vrms)	Irms ⁶ (A)
			100 MHz	400 MHz	500 MHz				
CM1394L_	0.813 @ 660 MHz	1.2	11.1	21.1	22.7	0.22	0.105	50	1.5

1. When ordering, please specify **packaging** code:

CM1394LC

- Packaging:** C = 7" machine-ready reel. EIA-481 embossed plastic tape (600 parts per full reel).
 B = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter C instead.
 D = 13" machine-ready reel. EIA-481 embossed plastic tape (2200 parts per full reel).

2. Frequency at which the differential mode attenuation equals -3 dB
 3. Inductance measured at 100 MHz
 4. DCR is specified per winding.
 5. Winding to winding isolation (hipot) tested for one minute.
 6. Current per winding that causes a 15°C rise from 25°C ambient.
 7. Electrical specifications at 25°C.
 Refer to Doc 362 "Soldering Surface Mount Components" before soldering.




Recommended Land Pattern

A max	B max	C max	D ref	E ref	F ref	G min	H
0.231	0.196	0.150	0.107	0.100	0.178	0.04	0.03
5,87	4,98	3,81	2,72	2,54	4,52	1,02	0,76




IEEE 1394 Common Mode Choke

Typical Attenuation (Ref: 50 Ohms)



Typical Impedance vs Frequency



US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 215-2 Revised 01/26/05

© Coilcraft Inc. 2017

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.