


# Shielded Power Inductors – EPL3012



- Low profile shielded power inductors; 3 × 3 × 1.3 mm max.
- Very low DCR, high SRF ratings, Isat ratings up to 2.0 A

**Designer's Kit C437** contains 5 each of all values

**Core material** Ferrite

**Core and winding loss** See [www.coilcraft.com/coreloss](http://www.coilcraft.com/coreloss)

**Environmental** RoHS compliant, halogen free

**Terminations** RoHS compliant tin-silver-copper (96.5/3/0.5) over tin over nickel over silver-platinum. Other terminations available at additional cost.

**Weight** 38 – 42 mg

**Ambient temperature** –40°C to +85°C with (40°C rise) Irms current.

**Maximum part temperature** +125°C (ambient + temp rise). **Derating.**

**Storage temperature** Component: –40°C to +125°C.

Tape and reel packaging: –40°C to +80°C

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Failures in Time (FIT) / Mean Time Between Failures (MTBF)**

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

**Packaging** 2000/7" reel; 7500/13" reel Plastic tape: 8 mm wide, 0.2 mm thick, 4 mm pocket spacing, 1.55 mm pocket depth

**PCB washing** Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787\\_PCB\\_Washing.pdf](#).

Part number <sup>1</sup>	Inductance <sup>2</sup> ±20% (µH)	DCR (Ohms) <sup>3</sup>		SRF typ <sup>4</sup> (MHz)	Isat (A) <sup>5</sup>			Irms (A) <sup>6</sup>	
		nom	max		10% drop	20% drop	30% drop	20°C rise	40°C rise
EPL3012-102ML_	1.0	0.060	0.066	110	0.85	1.4	2.0	1.7	2.2
EPL3012-152ML_	1.5	0.069	0.075	103	0.70	1.2	1.7	1.5	1.9
EPL3012-182ML_	1.8	0.076	0.084	92	0.65	1.1	1.6	1.4	1.8
EPL3012-222ML_	2.2	0.097	0.106	76	0.55	0.95	1.4	1.3	1.7
EPL3012-332ML_	3.3	0.136	0.150	62	0.50	0.90	1.1	1.1	1.4
EPL3012-472ML_	4.7	0.165	0.181	52	0.47	0.85	1.0	0.90	1.1
EPL3012-103ML_	10	0.316	0.348	32	0.34	0.59	0.80	0.60	0.79
EPL3012-223ML_	22	0.718	0.790	18	0.17	0.38	0.61	0.42	0.54

1. When ordering, please specify **packaging** code:

**EPL3012-223MLC**

**Packaging: C** = 7" machine-ready reel. EIA-481 embossed plastic tape (2000 parts per full reel).

**B** = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter C instead.

**D** = 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (7500 parts per full reel).

2. Inductance tested at 1 MHz, 0.1 Vrms, 0 Adc.

3. DCR measured on a micro-ohmmeter.

4. SRF measured using Agilent/HP 4395A network analyzer or equivalent.

5. DC current at 25°C that causes the specified inductance drop from its value without current. [Click for temperature derating information.](#)

6. Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings. [Click for temperature derating information.](#)

7. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



[www.coilcraft.com](http://www.coilcraft.com)

**US** +1-847-639-6400 [sales@coilcraft.com](mailto:sales@coilcraft.com)

**UK** +44-1236-730595 [sales@coilcraft-europe.com](mailto:sales@coilcraft-europe.com)

**Taiwan** +886-2-2264 3646 [sales@coilcraft.com.tw](mailto:sales@coilcraft.com.tw)

**China** +86-21-6218 8074 [sales@coilcraft.com.cn](mailto:sales@coilcraft.com.cn)

**Singapore** + 65-6484 8412 [sales@coilcraft.com.sg](mailto:sales@coilcraft.com.sg)

Document 692-1 Revised 01/05/17


© Coilcraft Inc. 2017

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.





# Shielded Power Inductors – EPL3012 Series

## L vs Current



## L vs Frequency



## Part Marking

Part number	Value	1st digit	2nd digit	Multiplier
EPL3012-102	1.0 µH	Brown	Black	Red
EPL3012-152	1.5 µH	Brown	Green	Red
EPL3012-182	1.8 µH	Brown	Gray	Red
EPL3012-222	2.2 µH	Red	Red	Red
EPL3012-332	3.3 µH	Orange	Orange	Red
EPL3012-472	4.7 µH	Yellow	Violet	Red
EPL3012-103	10 µH	Brown	Black	Orange
EPL3012-223	22 µH	Red	Red	Orange

Note: All marked parts have three dots. Black dot, used only on the -102 and -103 as second significant digit, may be very difficult to see.

## Recommended Land Pattern

Dimensions are in  $\frac{\text{inches}}{\text{mm}}$

Small surface blemishes are not unusual and do not adversely affect performance. Wire may be visible inside the voids.  
Acceptable void sizes:  
Top: 0.01 in / 0,254 mm × 0.01 in / 0,254 mm  
Sides: 0.02 in / 0,5 mm × 0.047 in / 1,2 mm



www.coilcraft.com

**US** +1-847-639-6400 sales@coilcraft.com  
**UK** +44-1236-730595 sales@coilcraft-europe.com  
**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw  
**China** +86-21-6218 8074 sales@coilcraft.com.cn  
**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 692-2 Revised 01/05/17

© Coilcraft Inc. 2017

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.