


SPICE Model – 0402DC

This lumped-element (SPICE) model data simulates the frequency-dependent behavior of Coilcraft RF surface mount inductors from 1 MHz to the upper frequency limit shown in the accompanying table.

The equivalent lumped element model schematic is shown below. The element values R1, R2, C, and L are listed for each component value. The value of the frequency-dependent variable resistor R_{VAR} relates to the skin effect and is calculated from:

$$R_{VAR} = k * \sqrt{f}$$

- k is shown for each value in the accompanying table.
- f is the frequency in Hz



The data represents de-embedded measurements, as described below. Effects due to different customer circuit board traces, board materials, ground planes or interactions with other components are not included and can have a significant effect when comparing the simulation to measurements of the inductors using typical production verification instruments and fixtures.

Each model should only be analyzed at the input and output ports. Individual elements of the model are not determined by parameter measurement. The elements are determined by the overall performance of the lumped element model compared to the measurements taken of the component.

Typically, the Self-Resonant Frequency (SRF) of the component model will be higher than the measurement of the component mounted on a circuit board. The parasitic reactive elements of a circuit board or fixture will effectively lower the circuit resonant frequency, especially for very small inductance values. Since data sheet specifications are based on typical production measurements, and the SPICE models are based on de-embedded measurements as described below, the model results may be different from the data sheet specifications.

Lumped Element Modeling Method

The measurements were made over a brass ground plane with each component centered over an air gap, as illustrated in Figure 1. The gap width for each size component is given in Table 1. The test pads were 30 mil

Table 1. Test Gap

Size	Gap Width (inch / mm)
0302	0.017 / 0.432
0402,0403	0.017 / 0.432
0603	0.026 / 0.660
0805	0.040 / 1.016
1008	0.060 / 1.524
1206	0.080 / 2.032
1812	0.120 / 3.048

(50 Ohm) wide traces of tinned gold over 25 mil thick alumina, and were not included in the gap. The TRL* calibration plane is also illustrated in Figure 1.




Figure 1. Test Setup

The lumped element values were determined by matching the simulation model to an average of the measurements. This method results in a model that represents as closely as possible the typical frequency-dependent behavior of the component up to a frequency just above the self-resonant frequency of the model.

The lumped element models were used to generate our 2-port S-parameters and therefore give identical results. The S-parameters are available on our web site at <http://www.coilcraft.com/models.cfm>.

Disclaimer

Coilcraft makes every attempt to provide accurate measurement data and software, representative of our components, in a usable format. Coilcraft, however, disclaims all warrants relating to the use of its data and software, whether expressed or implied, including without limitation any implied warranties of merchantability or fitness for a particular purpose. Coilcraft cannot and will not be liable for any special, incidental, consequential, indirect or similar damages occurring with the use of the data and/or software.

SPICE Model for Coilcraft 0402DC Chip Inductors

Part number	R1 (Ω)	R2 (Ω)	C (pF)	L (nH)	k	Upper limit (GHz)	Part number	R1 (Ω)	R2 (Ω)	C (pF)	L (nH)	k	Upper limit (GHz)
0402DC-3N0	13.30	0.0370	0.0380	3.00	5.500E-06	16	0402DC-22N	25.00	0.1900	0.0470	22.00	3.400E-05	8.0
0402DC-3N3	20.48	0.0370	0.0380	3.30	5.420E-06	15	0402DC-27N	25.00	0.1929	0.0460	27.00	5.700E-05	8.0
0402DC-3N6	22.00	0.0460	0.0390	3.60	5.580E-06	14	0402DC-30N	28.00	0.2450	0.0490	30.00	6.420E-05	8.0
0402DC-3N9	25.00	0.0460	0.0420	3.90	5.800E-06	14	0402DC-33N	28.00	0.2880	0.0440	33.00	6.960E-05	8.0
0402DC-4N3	25.00	0.0480	0.0310	4.30	8.040E-06	14	0402DC-39N	28.00	0.3750	0.0440	39.00	8.760E-05	8.0
0402DC-4N7	25.00	0.0480	0.0330	4.70	8.040E-06	13	0402DC-47N	28.00	0.4270	0.0480	46.74	1.156E-04	8.0
0402DC-5N6	25.00	0.0570	0.0380	5.60	9.040E-06	13	0402DC-51N	30.00	0.4320	0.0440	50.72	1.296E-04	8.0
0402DC-6N2	25.00	0.0570	0.0485	6.20	9.240E-06	13	0402DC-68N	30.00	0.9430	0.0480	67.50	1.746E-04	4.0
0402DC-6N8	25.00	0.0630	0.0370	6.80	1.144E-05	13	0402DC-72N	30.00	0.7870	0.0440	71.44	1.926E-04	4.0
0402DC-8N2	25.00	0.0700	0.0450	8.20	1.214E-05	13	0402DC-82N	30.00	1.057	0.0380	81.40	2.326E-04	4.0
0402DC-12N	25.00	0.0813	0.0490	12.00	2.210E-05	8.0	0402DC-91N	35.00	1.119	0.0350	90.40	2.772E-04	4.0
0402DC-15N	25.00	0.1150	0.0440	15.00	2.450E-05	8.0	0402DC-R10N	35.00	1.507	0.0450	99.00	2.532E-04	4.0
0402DC-18N	25.00	0.1379	0.0450	18.00	2.840E-05	8.0	0402DC-R12N	35.00	1.600	0.0440	119.0	3.342E-04	4.0



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 158-26 Revised 08/21/17

© Coilcraft Inc. 2017

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.