

NEW!

LLC Half-Bridge Transformers

For Isolated Gate Driver Bias Supply



- Low interwinding capacitance to minimize EMI and achieve high CMTI (Common Mode Transient Immunity)
- Optimized for isolated bias supplies for SiC and GaN gate drivers, such as the UCC25800-Q1 from Texas Instruments and the MPQ18913 from Monolithic Power Systems.
- Ideal for automotive OBC and traction Inverters in EV/HEV
- Designed and fabricated for systems mounted in harsh automotive conditions
- AEC-Q200 qualified

Core material Ferrite

Terminations RoHS compliant tin over nickel over silver glass frit.

Weight 0.53 – 0.54 g

Max part temperature +140°C

Ambient temperature -40°C to +125°C

Storage temperature Component: -40°C to +140°C.

Tape and reel packaging: -40°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Packaging 400/7" reel; 1200/13" reel Plastic tape: 24 mm wide, 0.4 mm thick, 8 mm pocket spacing, 5.5 mm pocket depth

PCB washing Tested with pure water or alcohol only. For other solvents, see [Doc787_PCB_Washing.pdf](#)

Part number ¹	Turns ratio Pri : Sec	Inductance ² ±30% (µH)		DCR max ³ (Ohms)		Leakage L ⁴ ±20% (µH)		Isolation ⁵ (VDC / Vrms)	Irms ⁶ (mA)	Volt-time ⁷ (V-µsec)	Cap ⁸ max (pF)
		Pri	Sec	Pri	Sec	Pri	Sec				
HTX8045C-753ARC	1 : 1	75	75	0.345	0.345	9.1	9.1	5000 / 3535	710	21.6	0.55
HTX8045C-104ARC	1 : 1	100	100	0.400	0.400	14.6	14.6	5000 / 3535	790	24.8	0.66
HTX8045C-114BRC	2.5 : 1	115	18	0.430	0.170	15.9	2.6	5000 / 3535	650	27.0	0.60
HTX8045C-124CRC	2 : 1	120	30	0.450	0.225	14.8	3.8	5000 / 3535	640	28.1	0.68
HTX8045C-104DRC	1.5 : 1	100	44	0.410	0.270	12.5	5.6	5000 / 3535	700	25.9	0.64
HTX8045C-104ERC	1.33 : 1	100	55	0.415	0.310	11.0	6.2	5000 / 3535	670	25.9	0.71
HTX8045C-104FRC	1.2 : 1	100	70	0.405	0.335	10.7	7.4	5000 / 3535	680	25.9	0.76

1. When ordering, please specify **turns ratio** and **packaging** codes:






HTX8045C-104FRC

Turns ratio: A = 1:1 B = 2.5:1 C = 2:1 D = 1.5:1
E = 1.33:1 F = 1.2:1

Packaging: C = 7" machine-ready reel. EIA-481 embossed plastic tape (400 parts per full reel). Quantities less than full reel available: in tape (not machine ready) or with leader and trailer (\$25 charge).

D = 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (1200 parts per full reel).

- Inductance measured at 100 kHz, 0.1 Vrms, 0 ADC on an HP4263B (or equivalent).
 - DCR is measured on a HP4263B (or equivalent).
 - Leakage Inductance LL is measured at 100 KHz, 0.1 Vrms with other windings shorted.
 - 5000 VDC, 3535 Vrms; one minute isolation (hipot) measured between primary and secondary. 5.9 mm creepage and clearance Material Group IIIa (175 ≤ CTI < 400).
 - Current that causes a 40°C rise from 25°C when applied to the primary winding with secondary current defined by the turns ratio.
 - Volt-time is for reference and calculated with 2400 Gauss.
 - Interwinding capacitance is measured at 250 kHz, 0.1 Vrms across pins 1-4 with pins 2 and 3 open.
 - Electrical specifications at 25°C.
- Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



Dimensions are in inches/mm

Recommended Land Pattern



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 1818-1 Revised 01/06/26

© Coilcraft Inc. 2026

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.